



**SOLVAY**

asking more from chemistry®



# Electronic Wet Chemicals Packaging Data

# H<sub>2</sub>O<sub>2</sub> Hydrogen Peroxide

		INTEROX® EG-ST 30 – 59 %	INTEROX® EG-10 30 – 32 %	INTEROX® EG-1 30 – 32 %	INTEROX® Pico 30 – 32 %	INTEROX® PicoPlus 30 – 32 %
<b>60 I Drum</b> 65 kg Mauser	PE Pallet 6 drums	✓	✓			
<b>200 I Drum</b> 210 kg Mauser	PE Pallet 2 drums	✓	✓			
w or w/o dip tubes						
<b>200 I Drum</b> 210 kg Rikutec		✓	✓	✓	✓	✓
w or w/o dip tubes						
<b>1,000 I IBC</b> 1,100 kg Mauser		✓	✓			
w or w/o dip tubes						
<b>1,000 I IBC</b> 1,100 kg Rikutec		✓	✓	✓	✓	✓
w or w/o dip tubes						
<b>ISO TC 20 m<sup>3</sup></b> Polymer lined				✓	✓	✓
<b>ISO TC 20 m<sup>3</sup></b> Passivated steel		✓				

# H<sub>3</sub>PO<sub>4</sub> Phosphoric Acid

		H <sub>3</sub> PO <sub>4</sub> Grade 1 79–81% and 84–86%	H <sub>3</sub> PO <sub>4</sub> Grade 2 79–81% and 84–86%
<b>200l Drum</b> 300 kg – 320 kg Mauser PE Pallet 2 drums w or w/o dip tubes		✓	✓
<b>200l Drum</b> 300 kg – 320 kg Rikutec PE Pallet 2 drums w or w/o dip tubes			✓
<b>1,000l IBC</b> 1,300 kg Mauser w or w/o dip tubes		✓	✓
<b>1,000l IBC</b> 1,300 kg Rikutec w or w/o dip tubes			✓

# H<sub>2</sub>O<sub>2</sub> Packaging Data



## INTEROX® EG-ST / INTEROX® EG-10

### PE Drum Mauser

Height	350 mm
Diameter	400 mm
Filling volume	60 liter
Tare weight	0.64 kg



## INTEROX® EG-ST / INTEROX® EG-10

### PE Drum Mauser

Height	945 mm
Diameter	578 mm
Filling volume	200 liter
Tare weight	14 kg



## INTEROX® EG-ST / INTEROX® EG-10 INTEROX® EG-1 / INTEROX® Pico INTEROX® PicoPlus

### PE Drum Rikutec

Height	955 mm
Diameter	581 mm
Filling volume	200 liter
Tare weight	16.5 kg

# H<sub>2</sub>O<sub>2</sub> Packaging Data



## INTEROX® EG-ST / INTEROX® EG-10

### IBC Single Walled Mauser

Height	1,200 mm
Width	1,000 mm
Depth	1,151 mm
Filling volume	1,000 liter
Tare weight	65 kg



## INTEROX® EG-ST / INTEROX® EG-10 INTEROX® EG-1 / INTEROX® Pico INTEROX® PicoPlus

### IBC Double Walled Rikutec

Height	1,200 mm
Width	1,000 mm
Depth	1,165 mm
Filling volume	1,000 liter
Tare weight	95 kg



## INTEROX® EG-ST

### ISO Tank Unlined Passivated Stainless Steel

Filling volume	20,000 liter
----------------	--------------



## INTEROX® EG-1 / INTEROX® Pico INTEROX® PicoPlus

### ISO Tank Lined with PTFE

Filling volume	20,000 liter
----------------	--------------

# H<sub>3</sub>PO<sub>4</sub> Packaging Data



**Grade 1 79 – 81% and 84 – 86%**  
**Grade 2 79 – 81% and 84 – 86%**

## PE Drum Mauser

Height	945 mm
Diameter	578 mm
Filling volume	200 liter
Tare weight	14 kg



**Grade 2 79 – 81% and 84 – 86%**

## PE Drum Rikutec

Height	955 mm
Diameter	581 mm
Filling volume	200 liter
Tare weight	16.5 kg



**Grade 1 79 – 81% and 84 – 86%**  
**Grade 2 79 – 81% and 84 – 86%**

## IBC Single Walled Mauser

Height	1,200 mm
Width	1,000 mm
Depth	1,151 mm
Filling volume	1,000 liter
Tare weight	65 kg



**Grade 2 79 – 81% and 84 – 86%**

## IBC Double Walled Rikutec

Height	1,200 mm
Width	1,000 mm
Depth	1,165 mm
Filling volume	1,000 liter
Tare weight	95 kg

# Pallets Packaging Data



## Six PE Drums 60 l Mauser

Filling volume 6 x 60 liter  
Pallet 1,200 x 800 mm



## Two PE Drums 200 l Mauser

Filling volume 2 x 200 liter  
Pallet 1,200 x 800 mm



## Two PE Drums 200 l Rikutec

Filling volume 2 x 200 liter  
Pallet 1,200 x 800 mm



#### Europe

**Solvay Fluor GmbH**  
Postfach 220  
30002 Hannover, Germany  
Telephone: +49 511 857-0  
Fax: +49 511 857-2146

#### North America

**Solvay Fluorides, LLC**  
3737 Buffalo Speedway,  
Suite 800,  
Houston, TX 77098, USA  
Telephone: +1 713 525-6000  
Fax: +1 713 525-7805

#### Asia/Pacific

**Solvay**  
EWAH University  
Industry Building 4th Fl.  
150, Bukahyun-ro,  
Soedaemun-ku  
Seoul 120-140 Korea  
Telephone: +82 2 2125 5306  
Fax: +82 2 2125 5380