

Specialty Polymers Certified for Contact with Drinking Water

For more than 20 years, Solvay has been helping water-handling device manufacturers discover the cost and performance advantages of using high-performance plastics in pressurized hot water systems. They can cost-effectively outperform brass and copper and have a proven track record of reliable performance.

Performance You Can Trust

Solvay voluntarily certifies its specialty polymers on a global basis to help OEMs expedite the approval process required for applications involving contact with drinking water (see Table 1). The wide range of products and grades that meet these requirements give designers maximum freedom in selecting the best material for a variety of applications, including:

- Pipes
- Flexible pipes
- Fittings
- Cartridges

- Valves
- · Faucet components
- Boiler components
- Pump components

Table 1: Specialty polymers certified for contact with drinking water

Polymer	Color NSF61*	W270 DVGW	KTW	ACS	WRAS	DM174
Amodel® PPA						
DW-1130 BK938	Black ✓ •	✓	$\checkmark \bullet \bullet \bullet$	✓	✓ •	
DW-1140 BK938	Black ✓ •	✓	√ • • •	✓	✓ •	
DW-1150 BK938	Black ✓ •	✓	✓ • • •	✓	✓ •	
A-1145 NT DW	Natural ✓ •					
Ixef® PARA						
DW-1022 BK001	Black ✓ •	✓	✓ • •	✓	✓ •	
DW-1022 NT000	Natural ✓ •	✓	✓ • •	✓	✓ •	
DW-1032 BK001	Black ✓ •	✓	✓ • •	✓	✓ •	
Omnix® HPPA						
DW-4050 BK001	Black ✓ •	✓	✓ • •	✓	✓ •	
DW-4050 NT000	Natural ✓ •	✓	✓ • •	✓	✓ •	

Certified for: • cold water (23 °C) • warm water (60 °C) • hot water (82-85 °C)

^{*} For some grades, certification NSF 61 is restricted to a maximum surface area to volume ratio. Please contact Solvay's technical representative for more details. Additional products and colors certified for drinking water contact are available.

Polymer	Color	NSF61*	W270 DVGW	KTW	ACS	WRAS	DM174
Solef® PVDF							
1008/0001	Natural	✓ •	✓	√ • • •		✓ •	
1010/0001	Natural	✓ •	✓	√ • • •	✓	✓ •	
1010/0901	Black	✓ •	✓	√ • • •		✓ •	
6008/0001	Natural	✓ •					
6010/0001	Natural	✓ •					
6012/0000	Natural	✓ •					
42308/0001E	Natural		✓	√ • • •	✓		
Udel® PSU							
GF-110 NT	Natural	✓ •	✓			✓ •	
GF-120 BK937	Black	✓ •	✓	√ • • •	✓	✓ •	
GF-120 NT	Natural	✓ •	✓	✓ • • •	✓	✓ •	
GF-130 BK937	Black	✓ •		✓ • • •			
P-1700 BK937	Black	✓ •	✓	√ • • •		✓ •	
P-1700 GY8057	Gray	✓ •	✓	√ • • •		✓ •	
P-1700 NT11	Transparent	✓ •	✓	√ • • •		✓ •	
P-1700 WH7407	White	✓ •	✓	√ • • •	✓	✓ •	
P-1710 NT15	Natural	✓ •					
P-3500 NT11	Transparent	✓ •		√ • • •			
P-3500 NT LCD	Transparent	✓ •	✓	√ • • •	✓	✓ •	
Veradel® PESU							
AG-320 NT	Natural					✓ •	
AG-330 NT	Natural		✓		✓	✓ •	
3330 GF	Natural	✓ •	✓	√ • • •	✓	✓ •	
3320 GF	Natural	✓ •					
A-101 NT	Natural	✓ •					
A-201 NT		✓ •					
A-301 NT		✓ •					
3100		✓ •					
3200		✓ •					
Acudel® mod. PPSU							
22000 BK937	Black	✓ •				✓ •	
22000 NT15	Natural	✓ •				✓ •	
Radel® PPSU							
R-5000 NT	Transparent	✓ •	✓	√ • • •	✓	✓ •	✓
R-5100 BK937	Black	✓ •	✓	✓ • • •	✓	✓ •	✓
R-5100 BU1197	Blue	✓ •	✓	✓ • • •	✓	✓ •	✓
R-5100 GY1037	Gray	✓ •	✓	√ • • •	✓	✓ •	✓
R-5100 NT15	Natural	✓ •	✓	✓ • • •	✓	✓ •	✓
R-5500 NT	Transparent	✓ •	✓	✓ • • •	✓	✓ •	✓

^{*} For some grades, certification NSF 61 is restricted to a maximum surface area to volume ratio. Please contact Solvay's technical representative for more details.

Additional products and colors certified for drinking water contact are available.

Certified for: • cold water (23 °C) • warm water (60 °C) • hot water (82−85 °C)

Color NSF61*	W270 DVGW	KTW	ACS	WRAS	DM174
Natural 🗸 •					
Black ✓ •					
Natural ✓ •	✓	√ • • •	✓	✓ •	✓
Black ✓ •	✓	√ • • •	✓	✓ •	✓
Natural ✓ •	✓	✓ • • •	✓	✓ •	✓
Black ✓ •	✓	√ • • •	✓	✓ •	✓
Black				✓ •	
Black ✓ •	✓	✓ • • •	✓	✓ •	✓
	✓			✓ •	
				✓ •	
	Natural Black Natural Black Natural Black Black Black Black Black Black Black Black Black	Natural Black Natural Black Natural Black Natural Black Black Black Black Black Black Black	Natural Black Natural Natural Natural Black Natural Natural	Natural ✓ ● Black ✓ ● Natural ✓ ● ✓ Black ✓ ● ✓ Natural ✓ ● ✓ Black ✓ ● ✓ Black ✓ ✓	Natural ✓ ● Black ✓ ● Natural ✓ ● Black ✓ ● Natural ✓ ● Black ✓ ● Black ✓ ● Black ✓ ● Black ✓ ●

Certified for: ● cold water (23 °C) ● warm water (60 °C) ● hot water (82 – 85 °C)

www.solvay.com

SpecialtyPolymers.EMEA@solvay.com | Europe, Middle East and Africa SpecialtyPolymers.Americas@solvay.com | Americas SpecialtyPolymers.Asia@solvay.com | Asia Pacific



Safety Data Sheets (SDS) are available by emailing us or contacting your sales representative. Always consult the appropriate SDS before using any of our products. Neither Solvay Specialty Polymers nor any of its affiliates makes any warranty, express or implied, including merchantability or fitness for use, or accepts any liability in connection with this product, related information or its use. Some applications of which Solvay's products may be proposed to be used are regulated or restricted by applicable laws and regulations or by national or international standards and in some cases by Solvay's recommendation, including applications of food/feed, water treatment, medical, pharmaceuticals, and personal care. Only products designated as part of the Solviva® family of biomaterials may be considered as candidates for use in implantable medical devices. The user alone must finally determine suitability of any information or products for any contemplated use in compliance with applicable law, the manner of use and whether any patents are infringed. The information and the products are for use by technically skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other substance or any other process. This is not a license under any patent or other proprietary right. All trademarks and registered trademarks are property of the companies that comprise Solvay Group or their respective owners.

^{*} For some grades, certification NSF 61 is restricted to a maximum surface area to volume ratio. Please contact Solvay's technical representative for more details.

Additional products and colors certified for drinking water contact are available.